



Cityline 300 – IDC Compact 11/22kW CityEV Safevolt® Public Charge Point

- **Smart enabled fast compact public and commercial charge point 11/22kW for integrations – three phase with Safevolt®**
- **ChargePost payment app – contactless option or client integration**
- Compact and durable stainless steel construction – OEM integration and door mount version
- CityEV back office management system – web access
- CityEV API and OCPP / OCPI support for CPO operations

The Cityline 300 IDC AC three phase 22kW charge point is designed for ease of installation on lamp columns or in lamp column doors. It is compact and lightweight and features built in CityEV Safevolt® and 6mA DC block.

The Cityline 300 IDC is fully smart (4G) and can be load managed by group making it ideal for on street deployment or in off-street car parks.

Payment can be made through the ChargePost app or charge sessions can be activated through fobs for fleet. The Cityline 300 IDC has an integrated NMI pattern approved meter.



Cityline 300 – IDC Specifications

Electrical	
Charge Current Rating	Min 6A – Max 32A, per phase
Charge Power Rating	Min 1380W – Max 22080W
Supply Voltage	230VAC +10% -6% (216V – 253V)/Phase – 380VAC
Required Supply Rating	Three Phase 32A per phase
EV Connector	
Type 2 Socket Connector	EN 62196-2 Type 2 socket with cover flap
Lock 'Smart' model	Locking socket
Can be used with CityEV cables or any standard Type 1/2 to Type 2 cable – car universal	
Charge Mode	
Charge Mode	Mode 3 fully compliant
Charge Power Control	
Maximum Charge Current	Up to 32A per phase
User Controls	
Display	Bright Tri-colour LED display indicators
Displayed Information	SYSTEM ● Ready/Busy/Fault APPROVAL ● Authorised/Pending CHARGE ● Charging/Charged/EV Fault
Remote data collection	Via CityEV SIM – 4G – API/OCPP 1.6/2.0.1 – CityEV CMS or customer back office
User Authorisation	
Local/Public	RFID Fob/ChargePost app – NFC and QR, contactless option
Safety Features	
EV Supply Disconnect	EV supply disconnected until EV properly connected
Safety	CityEV Safevolt® Automatic PME fault detection and 6mA DC block
Charge Current Limiter (Cable size validation)	Charge current automatically limited to connected cable size
Cable Fault Detection	EV Cable automatically checked for faults
EVSE Fault Monitor	Auto fault monitoring of contactor operation, supply, output and charge point internal operation
EV Fault Monitoring	EV communication fault monitor
Charge Current Monitor	EV charging current automatically monitored for under/over current conditions. EV Supply disconnected for over current faults
Mounting Options	
Mounting	Standard bolt and bespoke OEM integrations as required.
Column/post Mounting	Sealed integrated mounting option version for a range of situation types to accommodate, columns, doors, OEM integrations
Cable Entry	Internal concealed to connection unit
Environmental	
Enclosure Size	300 mm H x 100 mm W x 85 mm D – Weight 3–4 kg
Environmental Protection	Outdoor rated, protection to IP54
Vandal Resistance	IK8
Operating Temperature	-20°C to 55°C
Operating Humidity	10% to 100%



For further information
contact ChargePost on
(02) 6171 6108 or email
info@chargepost.com.au

ChargePost Pty Ltd,
39 Station Street,
Malvern VIC 3144 Australia
chargepost.com.au